

## United States Patent and Trademark Office



UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/528,738	03/22/2005	Yukihiro Hanaoka	24530-008/MXM	6966
32137 7590 12/10/2007 PATENT DOCKET CLERK COWAN, LIEBOWITZ & LATMAN, P.C.			EXAMINER	
			LOWE, MICHAEL S	
1133 AVENUE NEW YORK, 1	E OF THE AMERICAS NY 10036		ART UNIT	PAPER NUMBER
,		•	3652	¥**
		•	MAIL DATE	DELIVERY MODE
			12/10/2007	PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

	Application No.	Applicant(s)			
•	10/528,738	HANAOKA, YUKIHIRO			
Office Action Summary	Examiner	Art Unit			
	M. Scott Lowe	3652			
The MAILING DATE of this communication app	pears on the cover sheet with the c	orrespondence address			
Period for Reply					
A SHORTENED STATUTORY PERIOD FOR REPL' WHICHEVER IS LONGER, FROM THE MAILING D Extensions of time may be available under the provisions of 37 CFR 1.1 after SIX (6) MONTHS from the mailing date of this communication If NO period for reply is specified above, the maximum statutory period of Failure to reply within the set or extended period for reply will, by statute Any reply received by the Office later than three months after the mailing earned patent term adjustment. See 37 CFR 1.704(b).	ATE OF THIS COMMUNICATION 36(a). In no event, however, may a reply be tin will apply and will expire SIX (6) MONTHS from , cause the application to become ABANDONE	N. nely filed the mailing date of this communication. D (35 U.S.C. § 133).			
Status					
1) Responsive to communication(s) filed on					
2a) ☐ This action is <b>FINAL</b> . 2b) ☑ This	action is non-final.				
3) Since this application is in condition for allowance except for formal matters, prosecution as to the merits is					
closed in accordance with the practice under E	Ex parte Quayle, 1935 C.D. 11, 45	53 O.G. 213.			
Disposition of Claims					
<ul> <li>4)  Claim(s) 1-6 is/are pending in the application.</li> <li>4a) Of the above claim(s) is/are withdraw</li> <li>5)  Claim(s) is/are allowed.</li> <li>6)  Claim(s) 1-6 is/are rejected.</li> <li>7)  Claim(s) is/are objected to.</li> <li>8)  Claim(s) are subject to restriction and/o</li> </ul>					
Application Papers					
9) ☐ The specification is objected to by the Examine 10) ☑ The drawing(s) filed on 22 March 2005 is/are: Applicant may not request that any objection to the Replacement drawing sheet(s) including the correct 11) ☐ The oath or declaration is objected to by the Ex	a) $\square$ accepted or b) $\square$ objected to drawing(s) be held in abeyance. See ion is required if the drawing(s) is obj	ected to. See 37 CFR 1.121(d).			
Priority under 35 U.S.C. § 119					
12) Acknowledgment is made of a claim for foreign a) All b) Some * c) None of:  1. Certified copies of the priority documents 2. Certified copies of the priority documents 3. Copies of the certified copies of the prior application from the International Bureau * See the attached detailed Office action for a list	s have been received. s have been received in Application ity documents have been receive I (PCT Rule 17.2(a)).	on No d in this National Stage			
Attachment(s)					
1) ⊠ Notice of References Cited (PTO-892) 2) □ Notice of Draftsperson's Patent Drawing Review (PTO-948) 3) ☑ Information Disclosure Statement(s) (PTO/SB/08) Paper No(s)/Mail Date <u>5/2/05</u> .	4) Interview Summary Paper No(s)/Mail Da 5) Notice of Informal Pa 6) Other:	te			

Art Unit: 3652

5. " -- **L**P

## Claim Rejections - 35 USC § 112

The following is a quotation of the second paragraph of 35 U.S.C. 112:

The specification shall conclude with one or more claims particularly pointing out and distinctly claiming the subject matter which the applicant regards as his invention.

Claims 2,5 are rejected under 35 U.S.C. 112, second paragraph, as being indefinite for failing to particularly point out and distinctly claim the subject matter which applicant regards as the invention.

Claim 2 recites the limitation "the frame member" in line 5. There is insufficient antecedent basis for this limitation in the claim.

Claim 5 recites the limitation "the frame member" in line 22. There is insufficient antecedent basis for this limitation in the claim.

## Claim Rejections - 35 USC § 103

The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.

Claim 1 is rejected under 35 U.S.C. 103(a) as being unpatentable over Motoda (US 4,588,341) in view of Araake (GB 2337325A).

Re claim 1, Motoda teaches a stocker apparatus (generally 1) comprising: a first tray stock section (generally 11 or 16) capable of stocking a plurality of empty trays 20;

a second tray stock section (generally 11 or 16) capable of stocking a plurality of loaded

Art Unit: 3652

trays 20, the loaded trays being the empty trays loaded with products (not numbered); tray supporting means (generally 12,14,31,34,etc.) provided in said first tray stock section and said second tray stock section respectively for supporting the trays 20; lifting and lowering means for lifting and lowering said tray supporting means; and carrier means (generally 32) for carrying the loaded tray to said second tray stock section when the products are loaded on the empty tray existing in said first tray stock section, said apparatus further comprising an outer wall constituting member (not numbered) covering at least side surfaces and upper surfaces of said first trays stock section and said second tray stock section to separate said first tray stock section and said second tray stock section from an external atmosphere; an opening (generally 16 or 11) provided at an upper portion of said first tray stock section, said opening allowing the products to be carried in therethrough. Motoda is silent regarding an ionizer or air cleaning means. Araake teaches an ionizer (generally 5) provided near an opening, said ionizer jetting ionized air to the products carried in through said opening, and an air cleaning means (generally 10,6,etc.) provided at an upper portion (relative term) of said second tray stock section, said air cleaning means cleaning outside air and then introducing the air into said second tray stock section in order to keep the inside of the device cleaner and free of dust. It would have been obvious to one of ordinary skill in the art at the time the invention was made to have modified Motoda by the general teaching of Araake to have an ionizer provided near the opening, said ionizer jetting ionized air to the products carried in through said opening. and an air cleaning means provided at an upper portion of said second tray stock

Art Unit: 3652

section, said air cleaning means cleaning outside air and then introducing the air into said second tray stock section in order to keep the contents of the stocker cleaner and free of dust.

Claims 2,5 are rejected under 35 U.S.C. 103(a) as being unpatentable over Motoda (US 4,588,341) in view of Araake (GB 2337325A), and further in view of Schell (US 3,951,228).

Re claim 2, Motoda teaches said outer wall constituting member includes a frame (not numbered), a panel member (not numbered) and a pad (not numbered) but is silent regarding an elastically deformable sealing member. Schell teaches an enclosed, framed and paneled device with an elastically deformable sealing member (seal, grommet, generally 100,102,103,104,etc.) abutting on the frame in a longitudinal direction thereof, a panel member (various) abutting on the sealing member, and a pad member (various) abutting on the panel member in a manner to cover an outer edge thereof and fixedly attached to the frame member to thereby elastically hold the panel member with the sealing member therebetween in order to reduce noise, vibrations, leaks and keep proper compression of various elements. It would have been obvious to one of ordinary skill in the art at the time the invention was made to have modified Motoda by the general teaching of Schell to have an enclosed, framed and paneled device with an elastically deformable sealing member abutting on the frame in a longitudinal direction thereof, a panel member abutting on the sealing member, and a pad member abutting on the panel member in a manner to cover an outer edge thereof

Art Unit: 3652

and fixedly attached to the frame member to thereby elastically hold the panel member with the sealing member therebetween in order to reduce noise, vibrations, leaks and keep proper compression of various elements.

Re claim 5, Motoda teaches a stocker apparatus (generally 1) comprising:

a first tray stock section (generally 11 or 16) capable of stocking a plurality of empty
trays 20;

a second tray stock section (generally 11 or 16) capable of stocking a plurality of loaded

trays 20, the loaded trays being the empty trays loaded with products (not numbered); tray supporting means (generally 12,14,31,34,etc.) provided in said first tray stock section and said second tray stock section respectively for supporting the trays 20; lifting and lowering means for lifting and lowering said tray supporting means; and carrier means (generally 32) for carrying the loaded tray to said second tray stock section when the products are loaded on the empty tray existing in said first tray stock section, said apparatus further comprising an outer wall constituting member (not numbered) covering at least side surfaces and upper surfaces of said first trays stock section and said second tray stock section to separate said first tray stock section and said second tray stock section from an external atmosphere;

an opening (generally 16 or 11) provided at an upper portion of said first tray stock section, said opening allowing the products to be carried in therethrough. Motoda is silent regarding an ionizer or air cleaning means. Araake teaches an ionizer (generally 5) provided near an opening, said ionizer jetting ionized air to the products carried in through said opening, and an air cleaning means (generally 10,6,etc.) provided at an

upper portion (relative term) of said second tray stock section, said air cleaning means cleaning outside air and then introducing the air into said second tray stock section in order to keep the inside of the device cleaner and free of dust. It would have been obvious to one of ordinary skill in the art at the time the invention was made to have modified Motoda by the general teaching of Araake to have an ionizer provided near the opening, said ionizer jetting ionized air to the products carried in through said opening, and an air cleaning means provided at an upper portion of said second tray stock section, said air cleaning means cleaning outside air and then introducing the air into said second tray stock section in order to keep the contents of the stocker cleaner and free of dust.

Motoda teaches said outer wall constituting member includes a frame (not numbered), a panel member (not numbered) and a pad (not numbered) but is silent regarding an elastically deformable sealing member. Schell teaches an enclosed, framed and paneled device with an elastically deformable sealing member (seal, grommet, generally 100,102,103,104,etc.) abutting on the frame in a longitudinal direction thereof, a panel member (various) abutting on the sealing member, and a pad member (various) abutting on the panel member in a manner to cover an outer edge thereof and fixedly attached to the frame member to thereby elastically hold the panel member with the sealing member therebetween in order to reduce noise, vibrations, leaks and keep proper compression of various elements. It would have been obvious to one of ordinary skill in the art at the time the invention was made to have modified Motoda by the general teaching of Schell to have an enclosed, framed and paneled device with an

Art Unit: 3652

elastically deformable sealing member abutting on the frame in a longitudinal direction thereof, a panel member abutting on the sealing member, and a pad member abutting on the panel member in a manner to cover an outer edge thereof and fixedly attached to the frame member to thereby elastically hold the panel member with the sealing member therebetween in order to reduce noise, vibrations, leaks and keep proper compression of various elements.

Claims 3,4,6 are rejected under 35 U.S.C. 103(a) as being unpatentable over Motoda (US 4,588,341) in view of Araake (GB 2337325A), and further in view of Selusnik (US 3,974,922).

Re claim 3, Motoda teaches said lifting and lowering means may be any type of lift means (column 5, line 41). Selusnik teaches a tray lifting device (generally figure 3) with each of lifting and lowering means having four annular belts (generally 26) for supporting each of tray supporting means (generally 6,30) at four points, the annular belt being formed by superposing one end on another end of a straight belt having both the ends and fixedly holding the ends by a both end fixing member (general property of chain belts and the inherent connections between links, shown in figures), and the both end fixing member being located outside a winding round (various generally 22,24 area) of the annular belt in order to support heavier weights/trays and move at a faster speed. It would have been obvious to one of ordinary skill in the art at the time the invention was made to have modified Motoda by the teaching of Selusnik to have each of lifting and lowering means having four annular belts for supporting each of tray supporting

means at four points, the annular belt being formed by superposing one end on another end of a straight belt having both the ends and fixedly holding the ends by a both end fixing member, and the both end fixing member being located outside a winding round of the annular belt in order to support heavier weights/trays and move at a faster speed.

Re claim 4, Motoda as already modified by Selusnik teaches the straight belt being a straight toothed belt, and one end side or another end side of the straight toothed belt bent 180 degrees and then the one end side and the other end side are superposed and fixedly held by the both end fixing member.

Re claim 6, Motoda teaches a stocker apparatus (generally 1) comprising: a first tray stock section (generally 11 or 16) capable of stocking a plurality of empty trays 20;

a second tray stock section (generally 11 or 16) capable of stocking a plurality of loaded trays 20, the loaded trays being the empty trays loaded with products (not numbered); tray supporting means (generally 12,14,31,34,etc.) provided in said first tray stock section and said second tray stock section respectively for supporting the trays 20; lifting and lowering means for lifting and lowering said tray supporting means; and carrier means (generally 32) for carrying the loaded tray to said second tray stock section when the products are loaded on the empty tray existing in said first tray stock section, said apparatus further comprising an outer wall constituting member (not numbered) covering at least side surfaces and upper surfaces of said first trays stock section and said second tray stock section to separate said first tray stock section and said second tray stock section from an external atmosphere;

an opening (generally 16 or 11) provided at an upper portion of said first tray stock section, said opening allowing the products to be carried in therethrough. Motoda is silent regarding an ionizer or air cleaning means. Araake teaches an ionizer (generally 5) provided near an opening, said ionizer jetting ionized air to the products carried in through said opening, and an air cleaning means (generally 10,6,etc.) provided at an upper portion (relative term) of said second tray stock section, said air cleaning means cleaning outside air and then introducing the air into said second tray stock section in order to keep the inside of the device cleaner and free of dust. It would have been obvious to one of ordinary skill in the art at the time the invention was made to have modified Motoda by the general teaching of Araake to have an ionizer provided near the opening, said ionizer jetting ionized air to the products carried in through said opening. and an air cleaning means provided at an upper portion of said second tray stock section, said air cleaning means cleaning outside air and then introducing the air into said second tray stock section in order to keep the contents of the stocker cleaner and free of dust.

Motoda teaches said lifting and lowering means may be any type of lift means (column 5, line 41). Selusnik teaches a tray lifting device (generally figure 3) with each of lifting and lowering means having four annular belts (generally 26) for supporting each of tray supporting means (generally 6,30) at four points, the annular belt being formed by superposing one end on another end of a straight belt having both the ends and fixedly holding the ends by a both end fixing member (general property of chain belts and the inherent connections between links, shown in figures), and the both end fixing member

being located outside a winding round (various generally 22,24 area) of the annular belt in order to support heavier weights/trays and move at a faster speed. It would have been obvious to one of ordinary skill in the art at the time the invention was made to have modified Motoda by the teaching of Selusnik to have each of lifting and lowering means having four annular belts for supporting each of tray supporting means at four points, the annular belt being formed by superposing one end on another end of a straight belt having both the ends and fixedly holding the ends by a both end fixing member, and the both end fixing member being located outside a winding round of the annular belt in order to support heavier weights/trays and move at a faster speed.

Motoda as already modified by Selusnik teaches the straight belt being a straight toothed belt, and one end side or another end side of the straight toothed belt bent 180 degrees and then the one end side and the other end side are superposed and fixedly held by the both end fixing member.

## Conclusion

Any inquiry concerning this communication or earlier communications from the examiner should be directed to M. Scott Lowe whose telephone number is (571) 272-6929. The examiner can normally be reached on 6:30am-4:30pm M-Th.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Saul Rodriguez can be reached on (571)272-7097. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Page 11

Art Unit: 3652

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

Michael Lowe

Patent Examiner AU 3652

Michael Towe 11/30/07